COGELSA®
EFFICIENT LUBRICATION

*C/ Comercio, 36 – Polígono Industrial Can Sunyer*
*08740 SANT ANDREU DE LA BARCA ( Barcelona )*
*Telf: +34 93 6822220 – Fax: +34 93 6820055*
*www.cogelsa.com*
*e-mail: comercial@cogelsa.com, export@cogelsa.com*

# ТЕХНИЧЕСКИЙ ПАСПОРТ

## STANDARD SLIP – RANGE

### МАСЛО ДЛЯ СМАЗКИ НАПРАВЛЯЮЩИХ

**Описание:**

Масло на основе парафиновых минералов и присадок для улучшения его свойств.

**Применения:**

Специальное масло для смазки направляющих скольжения, систем циркуляции и общей смазки без разбрызгивания. Также для механизмов скольжения при высоких нагрузках, требующих масла с высокой вязкостью и адгезией.

**Характеристики:**

- Высокая несущая способность и противоизносные свойства.
- Специальные присадки позволяют смазывать направляющие скольжения с равномерной работой без вибрации, избегая эффекта прерывистого скольжения.
- Очень липкая формула для удержания масла в направляющих и механизмах скольжения.
- Отличная стойкость к окислению и антикоррозионные свойства.

**Уровень качества:**

− ISO 6743/4 - Категория L-HG
− DIN 51 524 Часть 2 (HLP)
− AFNOR NF E 48-603 (HM)
− CINCINATTI MILACRON P-53 (ISO VG 32) - CINCINATTI MILACRON P-47 (ISO VG 68) - CINCINATTI MILACRON P-50 (ISO VG 220)
− DIN 51 517 Часть 3 (CLP)



The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice.
Such information does not release the user from testing the product in their own application.
The data indicated represent average values and do not constitute product specifications.
For more information please contact COGELSA Technical Support.
COGELSA is not liable for damages caused by improper use of the product.

**CERTIFIED COMPANY**

ISO 9001
ISO 14001
BUREAU VERITAS
Certification

# STANDARD SLIP -RANGE

## Технические характеристики:

| ISO VG | | **32** | **68** | **100** | **150** | **220** | **320** | **1000** |
|---|---|---|---|---|---|---|---|---|
| Внешний вид | | прозрачный янтарь | | | | | | |
| Плотность при 15ºC. gr./cm$^3$ | ASTM D-1298 | 0,871 | 0,881 | 0,887 | 0,890 | 0,892 | 0,893 | 0,892 |
| Вязкость при 40ºC. ºC | ASTM D-445 | 32 | 67,5 | 98,4 | 159,2 | 225,3 | 326,0 | 952 |
| Индекс вязкости | ASTMD-2270 | 100 | 98 | 97 | 96 | 96 | 96 | 85 |
| Точка возгорания – открытая чаша, ºC | ASTM D-92 | 215 | 234 | 245 | 271 | 275 | 280 | 338 |
| Точка застывания, ºC | ASTM D-97 | -21 | -15 | -15 | -15 | -12 | -12 | -6 |
| FZG тест | DIN 51.354 | 11 | 12 | 12 | 12 | 12 | 12 | 12 |

Rev 08/15



The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice.
Such information does not release the user from testing the product in their own application.
The data indicated represent average values and do not constitute product specifications.
For more information please contact COGELSA Technical Support.
COGELSA is not liable for damages caused by improper use of the product.

**CERTIFIED COMPANY**